



Dimensions and Loads



Dimensions:

- A = 8' 6" (102")
- B = 22' 1" (265.0")
- C = 6' 2" (74")
- D = 16' (192")
- E = 4 Degree Load Angle
- Clearance of deck at transport height = 11"

Loads:

- 425 lbs. Tongue Load (Trailer)
- 1,075 lbs. Tongue Load (Cargo)
- 1,500 lbs. Total Tongue Load
- 768 lbs. Wheel Load (Trailer)
- 2,232 lbs. Wheel Load (Cargo)
- 3,000 lbs. Total Wheel Load
- Two (2), 6,000 lbs. Axles

Specifications and Features *(Base Trailer)*

- Ground to Travel Height
- GVWR 13,500 lbs.
- Payload Maximum 1,0000 lbs.
- Trailer Weight 3,500 lbs.
- 3 to 1 Payload to Trailer Weight Ratio
- Tires ST235/80R16LRE (3,520 lbs. Capacity Each)
- Aluminum Wheels
- Cylinders 3-1/2" Diameter x 12" Stroke
- Adjustable Ball Hitch 2-5/16" Diameter
- Ramp Built-in
- Larger Lockable Storage Compartment
- Controlled Descent
- Tie Down Rail Built-in

- DC Electric/Hydraulic Pump
- Tongue Jack
- Six (6) "D" Rings
- Breakaway Kit with Chains
- Electric Brakes Both Axles
- LED Lighting with 7 Pin Connector
- Single Pin Grounded 12 VDC Power Cable
- Control Switch with Cable
- HSLA Steel Construction (No Angle or Channel Iron)
- Grade 55 - 3/16" Diamond Plate Flooring
- Combination Hydraulic/Rubber Suspension

Options

- | | | | |
|--|-------|-----------------------------------|-------|
| On Board Power – includes Battery, Charger & Maintainer..... | 12784 | Spare Tire, Wheel & Carrier | 12544 |
| Cargo Winch 8,000 lbs. | 12785 | Special Paint | 12789 |
| Pintle Hitch (2-1/2" Lunette) | 12782 | (Yellow Paint Standard) | |
| Remote Power Option | 12783 | | |
| (Cord in addition to On Board Power) | | | |