

Lo-Riser IPT4-816 Trailer

Ground Level Loading to Travel Height




Features

- 4° Load Angle – No Ramps or Crowns
- Rubber over Hydraulic Suspension
- Safe, Simple, Swift, & Secure Loading /Unloading
- 2-Year Warranty

Lo-Riser IPT4-816 Trailer shown **below** at travel height. A mere 3/16" lip allows any rolling load to be easily pushed on or off the trailer deck. Nearly 1/2 of the trailer's framework rests on the ground for loading, supporting the weight of the payload and the additional weight of the forklift used for loading.



LO-RISER 4° INCLINING TRAILER



IPT4-816 - Part No. 12990

(A) Overall Width	(B) Overall Length	(C) Usable Deck Width	(D) Usable Deck Length	(E) Load Angle	Deck Height Typical
102" (259.1 cm)	265" (673 cm)	74" (188 cm)	192" (487.7 cm)	4°	18.25" (46.4 cm)

Loads & Weights:

- Payload Capacity 16,000 lbs (7,258 kg)
- GVWR 19,790 lbs (8,976 kg)
- Trailer Weight 3,790 lbs (1,719 kg)
- Load per axle 8,000 lbs (3,629 kg)
- Total Two-Axle Load 16,000 lbs (7,258 kg)
- Pintle Hitch (standard) Load 3,790 lbs (1,719 kg)

Trailer Frame:

- Frame (side) Rails are 3/8" (9.5 mm) Thick x 12" (305 mm) High (tapered at the rear end)
- Side Rails utilize distinctive shapes for unlimited tie-down locations
- Framework (cross-members) constructed of Grade 80, HSLA (high-strength low-alloy) Steel Plates - Formed to a 1.5" x 4" (38 x 102 mm) "L" Shape for maximum strength with minimum weight
- Cross-members are spaced on 10" (254 mm) centers for maximum strength – Preventing deck warping
- 3/16" (4.8 mm) Diamond Plate (Grade 55) Decking – Added strength and a non-slip surface

Electrical:

- LED Lighting with Dedicated Ground Circuit
- 7-Pin Round RV Connector
- Electric Brakes on all Axles

Misc.:

- On Board Power (Hyd. Pump, Battery, & 10 Amp Charger-Maintainer)
- Tires are 215 / 75R / 17.5H / 16 Ply / Rated 4,805 lbs @ 125 PSI @ 75 MPH

Options:

- Spare Tire and Carrier
- Special Paint Color (Black, Blue, and Yellow are standard colors)
- 12,000 lb (1,815 kg) Cargo Winch
- Extra D-Ring, Per Tie Down
- E-Track Package (48")
- Star Track Decking
- Solar Battery Charger
- 25K lbs. 2-5/16" Ball Coupler

Specifications may change without prior notice.



www.fourdegreetrailer.com | info@fourdegreetrailer.com

Four Degree Trailer Company
3726 US Hwy 34 | Kewanee, IL 61443
Toll-Free: 1-800-369-5365

A subsidiary of Rhino Tool Company



Scan QR for Videos



Form IPT4-816_10/18/22