fourdegreetrailer.com

Lift-A-Load EPT4-514 Trailer

Ground Level and Dock Height Loading/Unloading





The Lift-A-Load Trailer Deck remains level at all heights between ground level or dock height, for safe, easy loading and expedited delivery of low ground clearance and static loads.

Features

Level Loading up to 52" Dock Height

Rubber over Hydraulic Suspension

Minimal loading angle with integrated ramp


2-Year Warranty




Ground Level Loading









EPT4-514 - Part No. 17000

(A) Overall Width	(B) Overall Length	(C) Usable Deck Width	(D) Usable Deck Length	(E) Load Angle*	(F) Deck Height (Fully Raised)
102" (259 cm)	294" (747 cm)	74" (188 cm)	168" (427 cm)	8°	52" (132.08 cm)

*No load angle at dock height

Loads & Weights:

•	Payload Capacity	10,000 lbs	(4,536	kg)
•	GVWR	14,765 lbs	(6,697	kg)
•	Trailer Weight	4,765 lbs	(2161	kg)
•	Load per axle	6,000 lbs	(2,721	kg)
•	Hitch (standard) Load	2 748 lbs	(1 246	ka)

Trailer Frame:

- Frame (side) Rails are 3/16" (4.6 mm) ASTM 500 Grade B
- Side Rails utilize distinctive shapes for unlimited tiedown locations
- Framework (crossmembers) constructed of ASTM A36 Steel Plates - Formed to a 1.5" x 4" (38 x 102 mm) "L" Shape for maximum strength with minimum weight
- Crossmembers are spaced on 12" (305 mm) centers for maximum strength - Preventing deck warping
- 3/16" (4.8 mm) Diamond Plate (Grade 55) Decking -Added strength and a non-slip surface

Electrical:

- LED Lighting with Dedicated Ground Circuit
- 7-Pin Round RV Connector
- Electric Brakes on all Axles

Misc.:

- On Board Power (Hyd. Pump, Battery, & 10 Amp Charger-Maintainer)
- Tires are ST235/80R/16LRE / 10 Ply / Rated 3,520 lbs @ 80 PSI @ 75 MPH

Options:

- Spare Tire and Carrier
- · Special Paint Color (Black, Blue, and Yellow are standard colors)
- 8,000 lb (3,629 kg) Cargo Winch
- Extra D-Ring / Tie Downs
- E-Track Package (48" Height)
- · Star Track Decking
- · Aluminum Wheels
- Solar Battery Charger
- · Steel Side Boards with Built-In Tie Downs

Specifications may change without prior notice.



www.fourdegreetrailer.com | info@fourdegreetrailer.com

Four Degree Trailer Company

3726 US Hwy 34 | Kewanee, IL 61443 Toll-Free: 1-800-369-5365

A subsidiary of Rhino Tool Company

