# fourdegreetrailer.com

# **Lift-A-Load EPT4-716 Trailer**

**Ground Level and Dock Height Loading/Unloading** 





# **Features**

Level Loading up to 52" Dock Height

Rubber over Hydraulic Suspension

Minimal loading angle with integrated ramp

2-Year Warranty


The Lift-A-Load Trailer Deck remains level at all heights between ground level or dock height, for safe, easy loading and expedited delivery of low ground clearance and static loads.




Transport Level









### EPT4-716 - Part No. 17007

(A) Overall Width	(B) Overall Length	(C) Usable Deck Width	(D) Usable Deck Length	(E) Load Angle*	(F) Deck Height (Fully Raised)
102" (259 cm)	320" (813 cm)	68" (173 cm)	192" (488 cm)	9.5°	52" (132.08 cm)

\*No load angle at dock height

# Loads & Weights:

	•		
•	Payload Capacity 15,00	00 lbs	(6,804 kg)
•	GVWR21,41	2 lbs	(9,712 kg)
•	Trailer Weight 6,41	2 lbs	(2,908 kg)
•	Load per axle9,00	00 lbs	(4,082 kg)
•	Pintle Hitch (standard) Load 3,80	00 lbs	(1,724 kg)

### **Trailer Frame:**

- Frame (side) Rails are 3/16" (4.6 mm) ASTM 500 Grade B
- Side Rails utilize distinctive shapes for unlimited tiedown locations
- Framework (crossmembers) constructed of ASTM A36 Steel Plates - Formed to a 1.5" x 4" (38 x 102 mm) "L" Shape for maximum strength with minimum weight
- Crossmembers are spaced on 12" (305 mm) centers for maximum strength – Preventing deck warping
- 3/16" (4.8 mm) Diamond Plate (Grade 55) Decking Added strength and a non-slip surface

## Electrical:

- LED Lighting with Dedicated Ground Circuit
- 7-Pin Round RV Connector
- Electric Brakes on all Axles

#### Misc.:

- On Board Power (Hyd. Pump, Battery, & 10 Amp Charger-Maintainer)
- Tires are 215/75R/17.5H / 16 Ply / Rated 4,805 lbs
  25 PSI
  75 MPH

### **Options:**

- Spare Tire and Carrier
- Special Paint Color (Black, Blue, and Yellow are standard colors)
- 8,000 lb (3,629 kg) Cargo Winch
- Extra D-Ring / Tie Downs
- E-Track Package (48" Height)
- · Star Track Decking
- Solar Battery Charger
- Steel Side Boards with Built-In Tie Downs

Specifications may change without prior notice.



www.fourdegreetrailer.com | info@fourdegreetrailer.com

Four Degree Trailer Company 3726 US Hwy 34 | Kewanee, IL 61443 Toll-Free: 1-800-369-5365

A subsidiary of Rhino Tool Company





