

# Lo-Riser IPT4-716 Trailer

Ground Level Loading to Travel Height




## Features

- 4° Load Angle – No Ramps or Crowns
- Rubber over Hydraulic Suspension
- Safe, Simple, Swift, & Secure Loading /Unloading
- 2-Year Warranty

The mere 3/16" lip of the Lo-Riser IPT4-716 Trailer, allows any rolling load to be easily pushed on or off the trailer deck. Nearly ½ of the trailer's framework rests on the ground for loading, supporting the weight of the payload and the additional weight of the forklift used for loading. Trailer shown **below** at travel height.



# LO-RISER 4° INCLINING TRAILER



## IPT4-716 - Part No. 12780

(A) Overall Width	(B) Overall Length	(C) Usable Deck Width	(D) Usable Deck Length	(E) Load Angle	Deck Height Typical
102" (259.1 cm)	265" (673 cm)	74" (188 cm)	192" (487.7 cm)	4°	18.25" (46.4 cm)

### Loads & Weights:

- Payload Capacity ..... 14,000 lbs (6,350 kg)
- GVWR ..... 17,790 lbs (8,069 kg)
- Trailer Weight ..... 3,790 lbs (1,719 kg)
- Load per axle ..... 8,000 lbs (3,629 kg)
- Hitch (standard) Load..... 3,220 lbs (1,461 kg)

### Trailer Frame:

- Frame (side) Rails are 3/8" (9.5 mm) Thick x 12" (305 mm) High (tapered at the rear end)
- Side Rails utilize distinctive shapes for unlimited tie-down locations
- Framework (cross-members) constructed of Grade 80, HSLA (high-strength low-alloy) Steel Plates - Formed to a 1.5" x 4" (38 x 102 mm) "L" Shape for maximum strength with minimum weight
- Cross-members are spaced on 10" (254 mm) centers for maximum strength – Preventing deck warping
- 3/16" (4.8 mm) Diamond Plate (Grade 55) Decking – Added strength and a non-slip surface

### Electrical:

- LED Lighting with Dedicated Ground Circuit
- 7-Pin Round RV Connector
- Electric Brakes on all Axles

### Misc.:

- On Board Power (Hyd. Pump, Battery, & 10 Amp Charger-Maintainer)
- Tires are 215 / 75R / 17.5H / 16 Ply / Rated 4,805 lbs @ 125 PSI @ 75 MPH

### Options:

- Spare Tire and Carrier
- Special Paint Color (Black, Blue, and Yellow are standard colors)
- 8,000 lb (3,629 kg) Cargo Winch
- Extra D-Ring, Per Tie Down
- E-Track Package (48")
- Star Track Decking
- Solar Battery Charger
- Pintle Hitch 2 1/2"

Specifications may change without prior notice.



[www.fourdegreetrailer.com](http://www.fourdegreetrailer.com) | [info@fourdegreetrailer.com](mailto:info@fourdegreetrailer.com)

Four Degree Trailer Company  
3726 US Hwy 34 | Kewanee, IL 61443  
Toll-Free: 1-800-369-5365  
A subsidiary of Rhino Tool Company



Scan QR for Videos



Form IPT4-716\_12/12/22